DB-C8-J10-F2-1R

Product Details



Features

D-sub Connector, Junction shell (Plastic divided type, Straight clamp, Short screw #4-40UNC), DB

Part Number	DB-C8-J10-F2-1R
Status	Active
Number of Positions	-
Contact Pitch (mm)	
Rated Current (A)	
Rated Voltage (V)	
Applicable Specifications	
Waterproof/ Non-waterproof	
Applications	
Connector Type	Accessory
Connector Style	
Contact Type	
Wire Termination Style	
Applicable Wire Size (AWG)	
EMI Shielded	Applicable
PCB Mounting Style	
SMD Flag	

Applicable Wire Size (mm ²) Applicable Wire Size Dielectric Withstanding Voltage (VACr.m.s. Iminute) Insulation Resistance (millohm min.) Contact Resistance (millohm max.) Operating Temperature Range (deg. C) Shell Type Contact In Connecting Applicable Yine Size Finish of Contact in Connecting Area Finish of Contact in Connecting Applicable Yine Size Kounting Method Screw Lock Assembly Applicable Contacts Applicable Product Part Rome Applicable Contacts Applicable Contacts Applicable Contacts Applicable Product Part Rome Applicable Contacts	Shell Size	В
Dielectric Withstanding Voltage (VACr.m.s. 1minute) Insulation Resistance (megaohm min.) Contact Resistance (milliohm max.) Operating Temperature Range (deg. C) Shell Type Material of Insulator Finish of Contact in Connecting Area Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Method Screw Lock Assembly Fixistence of Ferrite Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant	Applicable Wire Size (mm ²)	
Voltage (VACr.m.s. 1 minute)Insulation Resistance (megaohm min.)Contact Resistance (milliohm max.)Operating Temperature Range (deg. C)Shell TypeAsterial of InsulatorContactContactFinish of Contact in Connecting AreaFinish of Contact in Connecting AreaShell TypeStorew Lock AssemblyFinish of FerriteApplicable ContactsApplicable ContactsContactStorew Lock AssemblyFinish of SpriteContact SpriteApplicable SpriteApplicable SpriteScow TypeApplicable SpriteApplicable Sprite<	Applicable Wire Size	
(negaohm min.)(negaohm min.)Contact Resistance (milliohm max.)Operating Temperature Range (deg. C)Shell TypeShell TypeMaterial of InsulatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting AreaStorew Lock AssemblyFixisher of FerriteApplicable Product Part NumbersAugusta AssemblyFixisher of SerriteApplicable Product Part NumbersAreasory TypeAreasory TypeRACH compliantHonding AreaServe Lock AssemblyServe Lock AssemblyServe Lock AssemblyApplicable Product Part NumbersRacessory TypeRace Locy Locy Locy Locy Locy Locy Locy Locy		
max.)Operating Temperature Range (deg. C)Shell TypeMaterial of InsultatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting AreaScrew Lock AssemblyFore Lock AssemblyApplicable ContactsApplicable Product Part NumbersRATE Screw Lock AsservitesApplicable ContactsApplicable ContactsApplicable ContactsRouting AreaBarbinsh AccessoriesApplicable ContactsRouting AreaBarbinsh AccessoriesApplicable ContactsApplicable ContactsRouting AreaBarbinsh AccessoriesApplicable ContactsApplicable Contacts <tr< th=""><th></th><th></th></tr<>		
(deg. C)Shell TypeMaterial of InsulatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting AreaMounting MethodScrew Lock AssemblyExistence of FerriteApplicable ContactsApplicable Product Part NumbersUse with AccessoriesAccessory TypeRAHS compliantIn Substances (2011/65/EU, (EU)2015/863)		
Material of InsulatorContactFinish of Contact in Connecting AreaFinish of Contact in PCB Mounting MethodScrew Lock AssemblyExistence of FerriteApplicable ContactsApplicable Product Part NumbersUse with AccessoriesAccessory TypeRAHS compliantEXACH compliant		
Contact Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Finishe of Ferrite Applicable Contacts Applicable Product Part Numbers Screws Lock Assembly Image: Strew Lock Assembly Applicable Product Part Numbers RACessory Type Rath Compliant Image: Strew Lock Assembly	Shell Type	
Finish of Contact in Connecting Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Lise with Accessories Accessory Type RoHS compliant KEACH compliant	Material of Insulator	
Area Finish of Contact in PCB Mounting Area Mounting Method Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant Use with Accessories	Contact	
Mounting AreaMounting MethodScrew Lock AssemblyExistence of FerriteApplicable ContactsApplicable Product Part NumbersUse with AccessoriesAccessory TypeRoHS compliantBACH compliant		
Screw Lock Assembly Existence of Ferrite Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant BACH compliant		
Existence of Ferrite Image: Contacts Applicable Contacts Image: Contacts Applicable Product Part Image: Contacts Numbers Image: Contacts Use with Accessories Image: Contacts Accessory Type Image: Contacts (Contacts	Mounting Method	
Applicable Contacts Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant ID substances (2011/65/EU, (EU)2015/863)	Screw Lock Assembly	
Applicable Product Part Numbers Use with Accessories Accessory Type RoHS compliant REACH compliant	Existence of Ferrite	
Numbers Use with Accessories Accessory Type RoHS compliant ID substances (2011/65/EU, (EU)2015/863)	Applicable Contacts	
Accessory Type RoHS compliant 10 substances (2011/65/EU, (EU)2015/863) REACH compliant		
RoHS compliant 10 substances (2011/65/EU, (EU)2015/863) REACH compliant	Use with Accessories	
REACH compliant	Accessory Type	
	RoHS compliant	10 substances (2011/65/EU, (EU)2015/863)
Remarks	REACH compliant	
	Remarks	

Notice

 The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

- 2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
- The products presented in this web site are designed for the uses recommended below. We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.
 - (1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that

you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

- (2) Recommended applications include:
 - * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc