JL04V-6A22-23SE-EB-R

Product Details



Features

Circular connector, connector standard EN61984, TÜV, Waterproof (when mated) type, 8 pos., Socket, Contact arrangement code: 22-23 , Straight plug

Part Number	JL04V-6A22-23SE-EB-R
Status	Active
Number of Positions	8 pos.
Rated Current (A)	23 A
Rated Voltage (AC Vr.m.s.)	250
Waterproof/ Non-waterproof	Waterproof (when mated)
Applications	Machine tools, Servomotors, Robots, Semiconductor Equipment, FA equipment, Industrial equipment, Rolling stock, Vessels, Telecommunications devices, Measurement equipment, Broadcast systems, Medical equipment, Computers and peripherals, and other electronic/ electric equipment.
Connector Type	Plug
Connector Style	Straight
Contact Type	Socket
Wire Termination Method	Soldering
Applicable Wire Size (AWG)	#12
Coupling Style	Threaded

Shell Size22Contact Arrangement Code22-23Contact Size X No. of Contacts#12*8Applicable Wire (Cross- sectional Area of Conductor) (mm² max.)3.5Alternative Insert Position (deg.)0Material of ContactCopper alloyFinish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)2Dielectric Withstanding voltage (VACr.m.s. Iminute)2,000Dielectric Withstanding (meg aohm min.)1,000Operating Temperature Range (deg. c)-55 Deg. Ct +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R.JL04-2022CK(**)-CR-R
Contact Size X No. of Contacts#12*8Applicable Wire (Cross- sectional Area of Conductor) (mm² max.)3.5Alternative Insert Position (deg.)0Material of ContactCopper alloyFinish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Dielectric Withstanding voltage (VACr.m.s. Iminute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. c)-55 Deg. Ct or +125 Deg. C.Applicable AccessoryJL04-2022CK(**)-R.JL04-2022CK(**)-CR-R
Applicable Wire (Cross- sectional Area of Conductor) (mm² max.)3.5Alternative Insert Position (deg.)0Material of ContactCopper alloyFinish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Contact Resistance (milliohm max.)2Dielectric Withstanding voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.).55 Deg. Cto +125 Deg. COperating Temperature Range (deg. c, o)JL04-2022CK(**)-CR-R
Sectional Area of Conductor) (mm² max.)3.5Alternative Insert Position (deg.)0Material of Contact0Material of ContactCopper alloyFinish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Dietectric Withstanding woltage (VACr.m.s. 1minute)2Dietectric Withstanding (megaohm min.)2,000Operating Temperature Range (deg. c)-55 Deg. Ct or +125 Deg. CApplicable AccessoryJL04-2022CK(**)-CR-R
(deg.)0Material of ContactCopper alloyFinish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Contact Resistance (milliohm max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-CR-R
Finish of Contact in Connecting AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Contact Resistance (milliohm max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
AreaSilver platingOuter Shell ColorBlack system interference colorTotal Current Rating (A)110.4Contact Resistance (milliohm max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
Total Current Rating (A)110.4Contact Resistance (milliohm max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
Contact Resistance (milliohm max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
max.)2Dielectric Withstanding Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
Voltage (VACr.m.s. 1minute)2,000Insulation Resistance (megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
(megaohm min.)1,000Operating Temperature Range (deg. C)-55 Deg. C to +125 Deg. CApplicable AccessoryJL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
-55 Deg. C to +125 Deg. C (deg. C) Applicable Accessory JL04-2022CK(**)-R,JL04-2022CK(**)-CR-R
Applicable Product Part
Numbers
Applicable Cable Diameter
RoHS compliant 10 substances (2011/65/EU, (EU)2015/863)
REACH compliant
Combination JL04V-2E22-23PE-B-R
Remarks

Notice

 The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

- 2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
- The products presented in this web site are designed for the uses recommended below. We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.
 - (1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that

you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

- (2) Recommended applications include:
 - * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc