

MX10-SG-PC2-1E-5000

Product Details



Part Number	MX10-SG-PC2-1E-5000
Status	Active(NRND)
Number of Positions	-
Connector Type	Contact
Connector Style	
Wire Termination Style	Crimp
PCB Side Mounting Style	
Material of Insulator	
Color of Insulator	
Material of Contact	Copper alloy
Finish of Contact in Connecting Area	Gold plating over Nickel
Finish of Contact in Terminal Area	Tin or Tin-Copper plating over Nickel
Finish of Contact in PCB Mounting Area	
Applicable Cable Type	AVS, AVSS, AVSS, AVSSX, AVX
Applicable Cable Conductive Area (mm ²)	0.3 (AVS), 0.3 to 0.85 (AVSS), 0.5 to 0.75 (AVSSX), 0.75(AVX)

Applicable Cable AWG No.	
Applicable Cable Sheath Diameter (mm)	
RoHS compliant	10 substances (2011/65/EU, (EU)2015/863)
REACH compliant	240 substances (23/01/2024)
Remarks	

Notice

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice.
Contact our sales staff for further information before considering or ordering any of our products.
For purchase, a product specification must be agreed upon.
2. Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry. Also contact us regarding the details of use, usage, specification before considering or ordering any of our products.
3. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.