## MX57B48NF1

## **Product Details**



## Features

0.64 (025) Non-waterproof SRS Connector, 48 pos. (Signal: 44, Mating detection: 4), Pin header

| Part Number            | MX57B48NF1                                |
|------------------------|---|
| Status                 | Active                                    |
| Number of Positions    | 48 pos. (Signal: 44, Mating detection: 4) |
| Connector Type         | Pin header                                |
| Connector Style        | Right angle                               |
| Wire Termination Style |   |
| PCB Mounting Method    | Soldering (Through-hole)                  |
| Applicable Wire        |   |
| Material of Insulator  | 40% GF PPS                                |
| Material of Terminal   | Brass                                     |
| Finish of Terminal     | Tin plating                               |
| RoHS compliant         | 10 substances (2011/65/EU, (EU)2015/863)  |
| REACH compliant        | 235 substances (14/06/2023)               |
| Remarks                |   |

 The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

- 2. Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry. Also contact us regarding the details of use, usage, specification before considering or ordering any of our products.
- 3. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.