N/MS3102A22-14SW

Product Details



Features

Circular connector compatible to MS standard, 19 pos., Contact Arrangement Code: 22-14, Panel mount receptacle, Socket

Part Number	N/MS3102A22-14SW
Status	Active
Number of Positions	19 pos.
Rated Current (A)	13 A
Rated Voltage (V)	700 VDC, 500 VAC
Waterproof/ Non-waterproof	Non-waterproof
Applications	Aircraft-related machines, industrial machinery, machine tools, factory automation machinery, communications components, broadcasting components, measuring equipment, medical products, computers and related components, and various other electronic and electrical components.
Connector Type	Receptacle
Connector Style	Panel mount
Contact Type	Socket
Wire Termination Method	Soldering
Applicable Wire Size (AWG)	#16 MAX.
Coupling Style	Threaded
Contact Size	#16
Shell Size	22

Contact Size X No. of Contacts#16*19Applicable Wire (cross- sectional Area of Conductor)1.25mm²₺₺ 下Applicable Wire Insulation Diameter (mm)6Atternative Insert Position (deg.)80Atternative Insert Position (deg.)80Finish of ContactCopper AlloyFinish of Contact in Connecting AreaSilver platingOuter Shell Color9Total Current Rating (A)49.4Dielectric Withstanding voltage (vAcr.m.s. 1minute)2000Insulation Resistance (megaohm min.)5000
sectional Area of Conductor) 1.25mm*£L* Applicable Wire Insulation
Diameter (mm)Alternative Insert Position (deg.)80Material of ContactCopper AlloyFinish of Contact in Connecting AreaSilver platingOuter Shell Color-Total Current Rating (A)49.4Dielectric Withstanding voltage (VACr.m.s. 1minute)2000Insulation Resistance (megaohm min.)5000
80Material of ContactCopper AlloyFinish of Contact in Connecting AreaSilver platingOuter Shell Color
Finish of Contact in Connecting AreaSilver platingOuter Shell Color
AreaSilver platingOuter Shell ColorTotal Current Rating (A)Contact Resistance (milliohm)Dielectric Withstanding Voltage (VACr.m.s. 1minute)Insulation Resistance (megaohm min.)
Total Current Rating (A)49.4Contact Resistance (milliohm)2000Dielectric Withstanding Voltage (VACr.m.s. 1minute)2000Insulation Resistance (megaohm min.)5000
Contact Resistance (milliohm) Dielectric Withstanding Voltage (VACr.m.s. 1minute) Insulation Resistance (megaohm min.)
Dielectric Withstanding 2000 Voltage (VACr.m.s. 1minute) 2000 Insulation Resistance 5000 (megaohm min.) 5000
Voltage (VACr.m.s. 1minute) 2000 Insulation Resistance (megaohm min.) 5000
(megaohm min.)
Mating Cycles (times)
Operating Temperature Range -55 deg. C to +125 deg. C (deg. C)
Applicable Contacts
Applicable Housing
Applicable Accessory
Applicable Product Part Numbers
Applicable Wire Diameter
RoHS compliant 10 substances (2011/65/EU, (EU)2015/863)
REACH compliant
Remarks

Notice

 The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

- 2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
- The products presented in this web site are designed for the uses recommended below. We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.
 - (1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that

you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that

you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

- (2) Recommended applications include:
 - * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc