

PS-10PE-D4LT1-LP1

Product Details



Features

Board to wire connector, with lock and eject bar, 2.54mm pitch, 2 rows, Mounting-side Contact Length 2.8mm, Right angle, 10 pos., Pin header

Part Number	PS-10PE-D4LT1-LP1
Status	Active
Number of Positions	10 pos.
Contact Pitch (mm)	2.54
Rated Current (A)	1
Connector Type	Pin header
Connector Style	Right angle
Contact Type	Pin
Wire Termination Style	-
Applicable Wire Size (AWG)	-
PCB Mounting Method	Soldering (Through-hole)
Number of Rows	2
Recommended PCB Thickness (mm)	1.6
Applicable Wire Insulation Diameter (mm)	-
Material of Contact	Copper alloy

(1) Applications that require consultation:

- * Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

- * We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

- * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc