

PS-26SM-D4P1-1D

Product Details



Features

Board to wire connector, conforming to MIL-DTL-83503 standard, F.R.C. insulation displacement MIL type, 2.54mm pitch, 2 rows, Daisy chain type, 26 pos., Socket connector

Part Number	PS-26SM-D4P1-1D
Status	Active
Number of Positions	26 pos.
Contact Pitch (mm)	2.54
Rated Current (A)	1
Connector Type	Socket connector
Connector Style	
Contact Type	Socket
Wire Termination Style	Insulation displacement
Applicable Wire Size (AWG)	1.27 mm pitch F.R.C. (#28 AWG or equivalent)
PCB Mounting Method	-
Number of Rows	2
Recommended PCB Thickness (mm)	-
Applicable Wire Insulation Diameter (mm)	1.1
Material of Contact	Copper alloy

3. The products presented in this web site are designed for the uses recommended below. We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

- * Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

- * We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

- * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc