

PS-60SD-D4C2

Product Details



Features

Board to wire connector, crimp type, 2.54mm pitch, 2 rows, 60 pos., Socket, Housing

Part Number	PS-60SD-D4C2
Status	Active
Number of Positions	60 pos.
Contact Pitch (mm)	2.54
Rated Current (A)	3
Connector Type	Socket housing
Connector Style	
Contact Type	Socket
Wire Termination Style	
PCB Mounting Method	
Number of Rows	2
Recommended PCB Thickness (mm)	
Applicable Cable Conductive Area (mm ²)	
Applicable Wire Insulation Diameter (mm)	

considering or ordering any of our products.

For purchase, a product specification must be agreed upon.

2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.

3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

- * Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

- * We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

- * Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc