

# PS-60SEN-D4P1-1C

## Product Details



### Features

Board to wire connector, with lock and eject bar, 2.54mm pitch, 2 rows, Closed end type, 60 pos., Socket connector

Part Number	PS-60SEN-D4P1-1C
Status	Active(NRND)
Number of Positions	60 pos.
Contact Pitch (mm)	2.54
Rated Current (A)	1
Connector Type	Socket connector
Connector Style	
Contact Type	Socket
Wire Termination Style	Insulation displacement
Applicable Wire Size (AWG)	1.27 mm pitch F.R.C. (#28 AWG or equivalent)
PCB Mounting Method	-
Number of Rows	2
Recommended PCB Thickness (mm)	-
Applicable Wire Insulation Diameter (mm)	1.1
Material of Contact	Beryllium copper



(1) Applications that require consultation:

- \* Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

- \* We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

- \* Computers, office appliances, telecommunications devices (terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc