

Technical drawing of a 24-pin D-sub connector. The drawing includes three views: a top view, a front view, and a side view. Key dimensions and features are labeled:

- Top View:** Shows the overall dimensions A, B, B', and C. It includes mounting holes with dimensions $2 \times M2.6 (P=0.45)$ and $2 \times M3 (P=0.5)$. A note "NOTE8" points to the pin array.
- Front View:** Shows the pin array with dimensions 5 ± 0.5 and 5.2 ± 0.5 . A note "NOTE7" points to the pin array.
- Side View:** Shows the profile of the connector with a note "NOTE1" pointing to the top edge.


The drawing is labeled "图面番号 (DRAWING NO.) SJ038406" in the top right corner.

SOCKET

PIN

A-A

7	FERRITE	1	FERRITE	—	—
6	SCREW LOCK	2	STEEL	NICKEL PLATE	M2. 6 (P=0. 45)
5	CONTACT #1	TABLE1	P:BRASS S:PHOSPHER BRONZE	NOTE 4	CONTACT AREA:0. 1 μ m MIN
4	CONTACT #2				
3	INSULATOR	1	PBT	(COLOR:BLACK)	—
2	SHELL	1	STEEL	NICKEL PLATE	—
1	ERTH LUG	2	STEEL	NICKEL PLATE	—
符号 NO.	名 称 DESCRIPTION	個 数 QTY	材 料 MATERIAL	仕 上 FINISH	備 考 REMARKS

仕様書 (SPECIFICATION) JACS-1045-22		第1版 (ORIGINAL DATE) 03/MAR/2003		尺度 (SCALE) 2:1	シリーズ (SERIES) Dsub	日本航空電子工業株式会社  JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.	A3 SIZE
一般公差 (GENERAL TOLERANCE)		製図 DR.	E. MURANO	名称 (TITLE) D※LC-J※※AF-10L6FE			
寸法 (DIMENSION)		担当 CHK.	Y. TAKAGI				
. ±		査閲 APPD.	—				
. × ±		承認 APPD.	Y. KUBOTA	質量 (MASS)		図面番号 (DRAWING NO.) SJ038406	版数 (VER.) 2
. × × ±		シート (SHEET NO.)					
. × × × +		単位 (UNIT) : mm					
		1 OF 1					