図面番号(DRAWING NO.) SJ112878

版数 VER.	年月日 DATE	CN NO.	変更内容 DESCRIPTION	製図 DR.	担当 CHK.	査閲 APPD.	承認 APPD.
2	13.Jan.2015	011907	ADD A NOTE.	-	Y.ITOU	-	T.KUDOU

WISDOM承認 2015/01/16







FIG.2 MATED CONDITION(REF.)
図2 嵌合状態図(参考)



FIG.1 CONTACT FORM (REF.)
図1 コンタクト形状(参考)

NOTE1. THREE 0.7mmHEIGHT BOSSES ARE SET TO NOTED PART.
2. CONTACT PLATING IS AS FOLLOWS:
・CONTACT AREA :REFLOW TIN OVER NICKEL
・SCREW AREA :NICKEL
3. THE COPPER APPEARS TO THE HATCHING AREA OF FIGURE 1.
4. THE LOT NUMBER IS PRINTED TO THIS AREA.
△5. RECOMMENDATION MOUNTING SCREW SIZE IS "M8".
THE SCREW-TIGHTENING TORQUE SHALL BE 10.0-12.5 N・m.

注1.本注記に示す箇所(全3ヶ所)に高さ0.7mmのﾎﾞｽを設ける。
2.コンタクトの表面処理は下記のようになる。
・接触部:Ni上リフローSn
・結線部:Ni
3.図1中の斜線部は銅素地が露出する。
4.図示の位置にロット番号を表示する。
△5.推奨取付ねじサイズﾞは、『M8』とする。取付ねじの締付トルクは、10.0～12.5N・mとする。

〈LOT NUMBER DISPLAY EXAMPLE ロット番号表示例〉

J12022
- PRODUCT CODE 製造コード
- YEAR (LAST DIGIT ONLY) 生産年(西暦末尾2桁)
- MONTH(1～9, OCT:O, NOV:X, DEC:Y) 生産月(1～9,10月:O, 11月:X, 12月:Y)
- DAY(01～31) 生産日 (NOTE4 注4参照)

〈RATED CURRENT AND RATED VOLTAGE DISPLAY EXAMPLE 定格電流、定格電圧 表示例〉 (NOTE4 注4参照)

100A/600V
- RATED CURRENT 定格電流
- RATED VOLTAGE 定格電圧

NO. 符号	DESCRIPTION 名称	QTY. 個数	MATERIAL 材料	FINISH 仕上	REMARKS 備考
2	HOUSING ハウシﾞング	1	GLASS FILLED PBT ｶﾞﾗｽ入りPBT	COLOR:BLACK 色相:黒色	
1	CONTACT コンタクト	1	COPPER ALLOY 銅合金	NOTE2 注2参照	NOTE3 注3参照

仕様書(SPECIFICATION): JACS-30265, △JAHL-30265
第1版(ORIGINAL DATE): 22.Oct.2012
尺度(SCALE): 1:1
シリーズ(SERIES): DW4
名称(TITLE): DW4P001ZF1
製図 DR.:
担当 CHK.: Y.ITOU
査閲 APPD.:
承認 APPD.: T.KUDOU
質量(MASS):
図面番号(DRAWING NO.): SJ112878
版数(VER.): 2
SIZE A2

一般公差(GENERAL TOLERANCE)
寸法(DIMENSION): .±0.8, .×±0.4, .××±0.1, .×××±
角度(ANGLES): ×°±, ×°×'±
単位(UNIT):mm

JAE CONNECTOR DIV. PROPRIETARY.
COPYRIGHT (C) 2012, JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.
JAE CONNECTOR.COM Reference Only

DCF-C-213H(12.08)
0 10 20 30 40 50 60 70 80 90 100