

SJ115419
(ON DRAWING)台異図

POLARIZING GROOVE
位置決めキー溝

NOTE3

NOTE1

NOTE2

1 3/16-18UNEF-2A

10 ±0.5

37.4 ±0.8

WHITE MARKING AS INDICATED (3 PARTS)
白マーキング表示 (3箇所)

(51.85)

φ42.2 ±0.8

22

40.65 ±0.8

注4

1 10 4 7 6 3 5 11 13 14

2

12

9 8

φ18 ±0.5

A-A

NOTE 1. CONTACT POSITION NUMBER APPEARS IN THE AREA SHOWN.
2. COMPANY LOGO “JAE” APPEARS IN THE AREA SHOWN.
3. INSERT ARRANGEMENT NUMBER “22-14P” IS MARKED IN THE AREA SHOWN.
4. PRODUCTION LOT NUMBER ARE MARKED AS INDICATED.

※※※

MANUFACTURING MONTH
(1 ~ 9 : X , Y , Z)
(JAN. ~ SEP. , OCT. , NOV. , DEC.)
MANUFACTURING YEAR (' 15 , ' 16 ...)

注1. 図示の位置に端子番号が表示されている。
2. 図示の位置に社名【JAE】、品名【JL10】が表示されている。
3. 図示の位置にインサート名【22-14P】が表示されている。
4. 図示の位置に製造ロットNo. を表示する。

※※※

製造月 (1~9月:1~9, 10月:X, 11月:Y, 12月:Z)
製造年 (' 15 , ' 16 ...)

DESIGNATION
命名法

JL10

8

A

22

-

14

P

※

※

-

EB

SERIES
シリーズ名

PLUG (ANGLE)
プラグ(アングル)

CLASS
嵌合時嵌合防水構造

SHELL SIZE
シェルサイズ

CONTACT ARRANGEMENT
インサート名

WITH END BELL
エンドベル付

INSERT ROTATING POSIRION
インサート回転角度
NONE:NORMAL POSITION
無し:ノーマルポジション

NONE:WITHOUT PROTECTIVE EARTH CONTACT
無し:保護回路構造無し

PIN CONTACT
ピンコンタクト

SPECIFICATION

NUMBER OF CONTACT:19×#16
RATED VOLTAGE:500VAC
RATED CURRENT:13A MAX. per CONTACT
APPLICABLE WIRE SIZE :1.25mm² MAX.

仕様

コンタクト: #16コンタクト19本
定格電圧 : 500VAC
定格電流 : 13A以下/1芯
適用電線 : 1.25mm²以下

14	END BELL	1	ALUMINUM ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
13	O-RING	1	SYNTHETIC RUBBER	—	
12	CONTACT	19	COPPER ALLOY	SILVER PLATING	
11	SET SCREW	1	STEEL	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
10	O-RING	1	SYNTHETIC RUBBER	—	
9	RETAINING RING	1	COPPER ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
8	RETAINING RING	1	COPPER ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
7	WAVE SPRING	1	STAINLESS STEEL	—	
6	C-TYPE RING	1	STAINLESS STEEL	—	
5	ASSEMBLY NUT	1	ALUMINUM ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
4	COUPLING NUT	1	ALUMINUM ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR
3	REAR INSULATOR	1	SYNTHETIC RESIN	—	COLOR:BLACK
2	FRONT INSULATOR	1	SYNTHETIC RESIN	—	COLOR:BLACK
1	BARREL	1	ALUMINUM ALLOY	ZINC PLATING	COLOR:BLACK SYSTEM INTERFERENCE COLOR

符号 NO.	名 称 DESCRIPTION	個 数 QTY.	材 料 MATERIAL	仕 上 FINISH	備 考 REMARKS
仕様書 (SPECIFICATION) JACS-50101					
一般公差 (GENERAL TOLERANCE)		第1版 (ORIGINAL DATE) 06/DEC/2015		尺度 (SCALE) 1:1	
寸法 (DIMENSION)		製図 DR.		シリーズ (SERIES) JL10	
角度 (ANGLES)		担当 CHK.		名称 (TITLE) JL10-8A22-14P-EB	
単位 (UNIT) : mm		査閲 APPD.		質量 (MASS)	
		承認 APPD.		図面番号 (DRAWING NO.)	
				JAE	
				日本航空電子工業株式会社 JAPAN AVIATION ELECTRONICS INDUSTRY, LTD.	
				図面番号 (DRAWING NO.)	
				SJ115419	
				版数 (VER.)	
				1	

DCF-G-212H(12.08)

WISDOM承認 2015/12/08

JAE Connector DIV. Proprietary.Copyright(C) 2015, Japan Aviation Electronics Industry, LTD.