



NOTE1. TERMINAL POSITION IS SHOWN.  
NOTE2. IDENTIFICATION MARKING SPECIFICATION IS ADJUSTMENT NECESSARY.  
NOTE3. PCB SPECIFICATION IS SHOWN TABLE 1.  
NOTE4. THE DIAMETER TOLERANCE OF FINISH HOLE IS ADJUSTMENT NECESSARY

注1. 端子配列を示す。  
 注2. 識別マーキング仕様は要調整。  
 注3. 適用基板仕様を表1に示す。  
 注4. スルーホール仕上の径公差は要調整。

7	MALE TERMINAL-4 (Sn)	24	PHOSPHOR BRONZE	TIN PLATING	-
6	MALE TERMINAL-3 (Sn)	27	PHOSPHOR BRONZE	TIN PLATING	-
5	MALE TERMINAL-2 (Sn)	10	PHOSPHOR BRONZE	TIN PLATING	-
4	MALE TERMINAL-2 (Au)	18	PHOSPHOR BRONZE	SELECTIVE GOLD PLATING AND SELECTIVE TIN PLATING	-
3	MALE TERMINAL-1 (Sn)	5	PHOSPHOR BRONZE	TIN PLATING	-
2	MALE TERMINAL-1 (Au)	20	PHOSPHOR BRONZE	SELECTIVE GOLD PLATING AND SELECTIVE TIN PLATING	-
1	MALE HOUSING	1	PBT GF30	-	COLOR : YELLOW
序号	名 称	個 数	材 料	仕 上	備 考

[illegible]

JAE Connector DIV. Proprietary. Copyright (C) 2016, Japan Aviation Electronics Industry, LTD.

特別管理品目  
SPECIAL CONTROL ITEM  
MX (SRS)

↑ S/W